




Profil podłużny DP1330W



Rzędne projektowane	142.98 - 142.98 - 143.30 - 143.40 - 143.44 - 143.51 - 143.57 - 143.58 - 143.72 - 143.62 - 143.48 - 143.43 - 143.47 - 143.52 - 143.52 - 143.15 - 142.99 - 142.64 - 142.61 - 142.84 - 143.03 - 144.00 - 144.12 - 144.50 - 145.17 - 145.44 - 145.66 - 145.86 - 147.27 - 146.97 - 147.29 - 147.36 - 147.28 - 147.20 - 147.12 - 146.98 - 146.99 - 147.16 - 147.06 - 146.99 - 146.02 - 145.73 - 145.79 - 145.99 - 146.46 - 146.70 - 146.67 - 146.53 - 146.21 - 145.41 - 144.79 - 144.77 - 144.81 - 144.86 - 145.02 - 145.15 - 145.38 - 145.59 - 146.26 - 146.52 - 146.51 - 146.49 - 146.53 - 146.66 - 146.67 - 146.69 - 146.49 - 146.39 - 146.20 - 145.99 - 145.92 - 145.95 - 145.89 - 145.70 - 145.61 - 145.66 - 145.78 - 145.95 - 146.31 - 146.31 - 146.46 - 146.51 - 146.55 -
Rzędne istniejące	142.98 - 142.98 - 143.21 - 143.34 - 143.46 - 143.60 - 143.64 - 143.66 - 143.67 - 143.71 - 143.74 - 143.75 - 143.76 - 143.76 - 143.26 - 143.06 - 142.64 - 142.55 - 142.81 - 143.00 - 143.96 - 144.10 - 144.61 - 145.39 - 145.66 - 145.88 - 146.07 - 147.55 - 147.08 - 147.32 - 147.42 - 147.46 - 147.41 - 147.33 - 147.19 - 147.20 - 147.28 - 147.18 - 147.14 - 146.28 - 146.54 - 146.63 - 146.59 - 146.44 - 146.20 - 145.62 - 146.37 - 146.53 - 146.53 - 146.55 - 146.62 - 146.64 - 146.64 - 146.64 - 146.51 - 146.49 - 146.42 - 146.28 - 146.16 - 146.05 - 145.95 - 145.99 - 146.50 - 145.88 - 145.83 - 146.04 - 146.19 - 146.37 - 146.30 - 146.47 - 146.50 - 146.51 - 146.55 -
Pikietaż	0+000.00 0+000.01 0+032.17 0+042.04 0+053.19 0+077.21 0+088.24 0+100.00 0+148.19 0+163.39 0+172.17 0+187.17 0+191.77 0+199.15 0+200.00 0+232.96 0+238.72 0+252.94 0+281.74 0+291.86 0+300.00 0+342.13 0+350.12 0+375.49 0+400.00 0+406.44 0+411.17 0+415.75 0+461.67 0+500.00 0+515.48 0+557.21 0+660.72 0+668.79 0+687.71 0+693.26 0+700.00 0+739.30 0+740.75 0+775.69 0+800.00 0+804.28 0+861.61 0+986.21 0+600.00 0+936.81 0+962.71 0+988.54 1+000.00 1+012.47 1+027.94 1+059.44 1+100.00 1+116.43 1+131.14 1+146.51 1+165.21 1+174.23 1+190.86 1+200.00 1+229.36 1+256.36 1+259.22 1+263.86 1+281.86 1+298.86 1+300.00 1+303.14 1+326.85 1+331.86 1+347.86 1+400.00 1+418.86 1+430.46 1+447.26 1+464.36 1+485.36 1+500.00 1+540.06 1+562.06 1+582.75 1+593.00 1+594.63 1+601.95 1+609.93
Proste i łuki poziome	L = 32.17 m A = 58.00 L = 21.03 m R = 160.00 m L = 24.02 m A = 58.00 L = 21.03 m L = 100.91 m R = -220.00 m L = 39.57 m L = 53.15 m R = 210.00 m L = 58.26 m L = 65.63 m R = -300.00 m L = 45.92 m L = 207.12 m R = 350.00 m L = 70.51 m R = 3000.00 m L = 43.09 m L = 84.99 m R = -3000.00 m L = 43.92 m L = 279.87 m R = 200.00 m L = 11.63 m L = 18.25 m

 - teren istniejący (w osi projektowanej drogi)

 - projektowana profil podłużny drogi nr 133C